Technical Data Sheet

Topadd® - TP 401

TP-401 is a general PVC processing aid with proper molecular weight, it is mainly to promote fusion of PVC compound and can be applied in producing PVC opaque applications. It can be used in rigid PVC formulations to improve melt flowing, PVC gelation ability and surface quality. It has been widely used in the processing of various PVC products.

Tech Spec:

Index	Viscosity (η)	Appearance	Volatiles Content (%)	Sieve residue (30 mesh)
Product			_	
TP-401	3.5-4.2	White powder	≤1.2	≤2.0

Advantage:

- Excellent fusion promotion property
- Good cost-performance
- Good surface-glossness
- Good melt-flowability and high output

Application:

TP-401 is mainly to promote fusion of PVC compound and can be applied in producing PVC pipes, PVC pipe fitting, PVC sheet , PVC profiles and other rigid pvc products.

Package and Storage

25kg PP woven bag with PE liner or 20kg paper bag with PE liner
Should be stored in dry and ventilated storeroom. This product is non-dangerous.
For other operations, please refer to SDS instructions provided by the manufacturer.

www.novistagroup.com info@novistagroup.com +86-536-8206760

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.