



# Technical Data Sheet

## Topadd® TIM-810

### Description

Acrylic impact modifier TIM-810 is a type of copolymer with core-shell structure, it shows good impact strength, good weather-resistance.

### Advantage

- Promote fusion
- Improve impact strength
- Improve weather-resistance

### Tech Spec

Specification	Unit	Test standard	TIM-810
Appearance	--	--	White Flowing powder
Bulk density	g/cm3	GB/T 1636-2008	0.35-0.55
Sieve residue (30 mesh)	%	GB/T 2916	≤2.0
Volatile content	%	ASTM D5668	≤1.5

### Application

TIM-810 is suitable for all kinds of opaque PVC products, such as PVC profile,PVC pipe,pipe fitting and PVC fencing etc.

### Package and Storage

20 or 25kg PP woven bag with PE liner .

Should be stored in dry and ventilated storeroom. This product is non-dangerous.

For other operations, please refer to SDS instructions provided by the manufacturer.

[www.novistagroup.com](http://www.novistagroup.com)

[info@novistagroup.com](mailto:info@novistagroup.com)

+86-536-8206760

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.