

Plastic & polymer additives and solution supplier E:info@novistagroup.com I:www.novistagroup.com

# **Technical Data Sheet** ProFlame<sup>®</sup> AM-4 Halogen-free flame retardant for TPU

ProFlame AM-4 is a formulated eco-friendly halogen-free flame retardant mainly based on phosphorus and nitrogen.With special surface coating treatment,AM-4 has good compatibility with the substrate, little influence to the physical properties of the final product, excellent flame-retarding performance, and in compliance with EU RoHS regulation.

## Advantages:

1. achieving FR performance by both gas phase and solid phase mechanism

- 2. good colorability
- 3. no hydrolysis, no blooming
- 4. good processability
- 5. good physical and electrical properties
- 6. low smoke, no-toxic, no dripping
- 7. halogen-free, no harm to the environment and human body

## **Technical Data:**

Items	Spec
Appearance	White free-flowing powder
P content,%	≥20
Decomposition Temperature, °C (TGA 1%)	≥280
Moisture,%	≤0.5
Average particle size (um, D50)	≤8.0

## Usage:

Recommended dosage is 21-22% for polyether TPU to reach UL-94 1.6mm-V0.

## Package:

AM-2 is delivered in paper-plastic composite bag, net weight 20 or 25±0.1kg .

## Storage and transportation:

Minimum shelf life is 1	2 months stored in a dry and	ventilated warehouse.
+86-536-8206760	info@novistagroup.com	www.novistagroup.com

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.